

It all began in the 1880's

when the community of Alderlea (ALL-DER-LEE) was just a whistle stop on Canada's rugged west coast - today those early days of Alderlea live on in what is now the Cowichan Valley, home to Pacific Energy.

Alderlea woodstoves have redefined the centuries-old charm of the cast iron stove by wrapping a graceful cast iron profile around legendary Pacific Energy steel fireboxes. This innovation delivers both radiant and convection heat for powerful performance.

In true pioneer style, The Alderlea has a practical side – a large concealed cook top, food warming shelves, an air-wash for a clear view of the fire, and an easy cleaning innovative ash disposal system.

Powered by Pacific Energy's proven steel fireboxes, the Alderlea collection will provide many years of low-maintenance operation, while delivering the ease of use and exceptional heat that comes with over 30 years of woodburning experience.

For your assurance of warmth and peace of mind, we further our commitment to quality and innovation with Pacific Energy's Limited Lifetime Warranty – we know of no better cast iron woodstove guarantee.

SMALL

For heating up to 1500 sq ft. *

MEDIUM

For heating up to 2000 sq ft. *

LARGE

For heating up to 3000 sq ft. *

Heating capacity will vary depending on type of wood, floor plan, house layout, heat loss of home, and geographical location.

CONTENTS

Minimum Clearances......15



Efficient Wood Heating is good for the Environment

Wood heat is a responsible choice and is a renewable and sustainable fuel source which does not contribute to global warming. When wood is burned as a substitute for fossil fuels, the result is a net reduction in CO2 emissions.

By choosing a Pacific Energy woodstove and responsible wood heating, you are making a difference. For over 30 years, a strong dedication to the environment and woodheat science has made Pacific Energy a recognized leader in hearth product innovation and clean burn technology. Our unique firebox design and stainless steel encapsulated baffle system burn with results meeting and exceeding EPA and CSA Standards. Improving environmental performance and energy efficiency continues to be Pacific Energy's primary focus, giving you piece of mind that heating your home with a Pacific Energy Wood Stove or Insert means choosing a green home heating solution.





The Alderlea T4 in historic cast iron incorporates all the outstanding features of the larger Alderlea woodstoves – huge glass for a full view of the fire, a cook top for peace of mind



during power outages, powerful heat output, a high efficiency rating, and user friendly operation. An effective heater with old world charm.



STANDARD FEATURES

- Pacific Energy's legendary steel firebox
- Reliable, durable, non-catalytic technology
- Industry-leading limited lifetime warranty
- Rich metallic black cast iron finish
- Floating firebox for extended stove life
- Air wash system for super clean glass
- Concealed swing-out cook top, fits 6" x 13" pan
- Food warming shelves
- Easy cleaning innovative ash system and chute
- Close wall clearances, without added expense of heat shields
- Steel baffle and 304 Stainless Steel insulation cover
- Inside and outside combustion air capable
- Mobile home approved

OPTIONS

- Temperature actuated 125 cfm variable speed blower
- Right handed models available
- Screen Door



Heating	Capacity	1,500 sq.ft.*
HEAT	Cord Wood	56,000 BTU
HE	EPA Test Fuel	26,300 BTU
Efficien	cy (LHV)	80.7%
Emissio	ons	2.9 gm/hr.
Log Siz	е	18 inches Max.
	26" Flue diame	20.75"

 $^{{}^{\}star}\, \text{Figures will vary depending on type of wood, floor plan, house layout, heat loss of home, and geographical location.}$



box, the Alderlea T5 combines the very best features of both cast iron and steel stoves. Beauty and strength.

Elegant, historic cast iron styling that adds to the decor of any room, radiant and convective heat, huge glass for a full view



of your fire, a concealed cook top for peace of mind during power outages all in a proven easy-lighting, clean, long-burning heater with 30 years of wood stove technology behind it.



STANDARD FEATURES

- Pacific Energy's legendary steel firebox
- Reliable, durable, non-catalytic technology
- Industry-leading limited lifetime warranty
- Rich metallic black cast iron finish
- Floating firebox for extended stove life
- Air wash system for super clean glass
- Concealed swing-out cook top, fits 9" x 11" pan
- Food warming shelves
- Easy cleaning innovative ash system and chute
- Close wall clearances, without added expense of heat shields
- 304 Stainless Steel baffle, insulation cover and flame shield
- Inside and outside combustion air capable
- Mobile home approved

OPTIONS

- Temperature actuated 125 cfm variable speed blower
- Right handed models available
- Screen Door



Heating	Capacity	2,000 sq.ft.*
НЕАТ ОUTPUT	Cord Wood	72,000 BTU
HE	EPA Test Fuel	34,600 BTU
Efficien	cy (LHV)	82.6%
Emissio	ons	3.4 gm/hr.
Log Siz	е	18 inches Max.
A STATE OF THE PARTY OF THE PAR	25" Flue diam	28.5" 10.125" 29"

^{*} Figures will vary depending on type of wood, floor plan, house layout, heat loss of home, and geographical location.




Patented Extended Burn Technology (EBT) gives the Alderlea T6, the largest of the Alderlea cast iron stoves, all-night burns with maximum heating capacity.

Huge glass opens up the view of your fire. Large cook top surface comfortably fits a large casserole pan with warming

Cooktop and warming shelves.







STANDARD FEATURES

- Pacific Energy's legendary steel firebox
- Reliable, durable, non-catalytic technology
- Industry-leading limited lifetime warranty
- Rich metallic black cast iron finish
- Floating firebox for extended stove life
- Air wash system for super clean glass
- Extended Burn Technology (EBT)
- Concealed swing-out cook top, fits 12" x 15" pan
- Food warming shelves
- Easy cleaning innovative ash system and chute
- Close wall clearances, without added expense of heat shields
- 304 Stainless Steel baffle, insulation cover and flame shield
- Inside and outside combustion air capable
- Mobile home approved

OPTIONS

(See page 13 for


more about EBT)

- Temperature actuated 125 cfm variable speed blower
- Right handed models available
- Screen Door



Heating	Capacity	3,000 sq.ft.*
HEAT	Cord Wood	97,000 BTU
HE	EPA Test Fuel	34,501 BTU
Efficien	cy (LHV)	80.3%
Emissio	ons	3.56 gm/hr.
Log Siz	е	20 inches Max.
	29.25"	28.75" 8.5" 8.5" eter = 06"

 $^{{}^{\}star}\, \text{Figures will vary depending on type of wood, floor plan, house layout, heat loss of home, and geographical location.}$



1/4 M.S. + (1/4 Rough to 7'10)

For more than 30 years Pacific Energy has challenged, then exceeded the traditional assumptions about wood heat. Our history of innovation is evident in our industry-leading features, our choice of the finest materials, our close eye on environmental responsibility, and our commitment to creating efficient and convenient appliances that fit your style and warm your life.

The result is a series of industry firsts, accomplished through our on-going mission to provide you with the best possible wood burning technology.

First Glass Air Wash System

- because a beautiful fire should be seen

First Floating Firebox Design

longer stove life with unrestricted thermal expansion

First Air Tight Ash Removal System

- for quick, clean maintenance of your stove

First Extended Burn Technology

- maximum efficiency for longer burns



PACIFIC






Pacific Energy's **Floating Firebox** eliminates metal fatigue caused by expansion and contraction during heating and cooling. Many of the firebox components are manufactured with corrosion-resistant 304 Stainless Steel. This combination of innovation and attention to detail dramatically extends the life of your appliance.



The PACIFIC ENERGY Integrated Combustion System

- Boost Air
- 2 Main Combustion Air
- 3 Air-Wash System
- 4 Secondary Combustion Air
- 5 Radiant Heat
- 6 Convection Heat



Pacific Energy's patented

Extended Burn Technology is available exclusively on T6 wood stoves. EBT regulates the flow of combustion air throughout the burn cycle and increases burn time. With EBT, your T6 will burn longer between loads and deliver more efficient fuel consumption.

US Patent #6,041,770





FLOOR PROTECTOR

STRAIGHT HEARTH

CORNER HEARTH

The charts shown below give the required dimensions of floor protector sizes based on various appliance installations.





CANADA

Non-combustible ember protection must be used. (Check local building codes for acceptable construction materials.) This protection must be under the stove and must extend 18" on the firing side and 8" to the other sides.

STRAIGHT HEARTH	ALDEI	RLEA T4	ALDE	RLEA T5	ALDERLEA T6			
(Extended to wall)	Α	В	Α	В	Α	В		
Minimum	40"	43 1/4"	40"	50 1/2"	41 1/2"	51 1/8"		
Residential, single wall, vertical connector	40"	50 1/4"	40"	54 1/2"	41 1/2"	52 1/8"		
Residential, single wall, horizontal connector	40"	48 1/4"	40"	50 1/2"	41 1/2"	53 1/8"		
Residential, double wall, vertical connector	40"	42 1/4"	40"	47 1/2"	41 1/2"	49 1/8"		
Residential, double wall, horizontal connector	40"	42 1/4"	40"	47 1/2"	41 1/2"	53 1/8"		
Alcove, double wall, connector	40""	46 1/4"	40"	52 1/2"	41 1/2"	52 1/8"		
Mobile home	40"	47 1/4"	40"	50 1/2"	41 1/2"	50 1/8"		

CORNER HEARTH		ALDEF	RLEA T4			ALDEF	RLEA T5		ALDERLEA T6				
(Extended to wall)	Α	C	D	E	Α	C	D	E	Α	C	D	E	
Minimum	40"	58 1/8"	55 1/4"	27"	40"	63 5/8"	59 1/8"	30 7/8"	41 1/2"	63 5/8"	59 1/8"	30 7/8"	
Residential, single wall, vert/horz connector	40"	60 7/8"	57 1/4"	29"	40"	67 7/8"	62 1/8"	33 7/8"	41 1/2"	61"	57 3/4"	28 3/8"	
Residential, double wall, vert/horz connector	40"	51"	50 1/4"	22"	40"	58"	55 1/8"	26 7/8"	41 1/2"	61"	57 3/4"	28 3/8"	
Mobile home	40"	58 1/8"	55 1/4"	27"	40"	63 5/8"	59 1/8"	30 7/8"	41 1/2"	62 3/8"	58 3/4"	29 3/8"	

USA

Non-combustible ember protection must be used. (Check local building codes for acceptable construction materials.)


This protection must be under the stove and must extend 16" to the front and 8" to the sides of the fuel loading door opening.


This protection is also required under the chimney connector and 2" beyond each side.


STRAIGHT HEARTH	ALDER	RLEA T4	ALDER	LEA T5	ALDERLEA T6			
(Extended to wall)	Α	В	Α	В	Α	В		
Minimum	32"	33 1/4"	34"	40 1/2"	36"	40 1/2"		
Residential, single wall, vertical connector	32"	48 1/4"	34"	52 1/2"	36"	49 1/2"		
Residential, single wall, horizontal connector	32"	46 1/4"	34"	48 1/2"	36"	50 1/2"		
Residential, double wall, vertical connector	32"	40 1/4"	34"	45 1/2"	36"	46 1/2"		
Residential, double wall, horizontal connector	32"	40 1/4"	34"	45 1/2"	36"	50 1/2"		
Alcove, double wall, connector	32"	44 1/4"	34"	50 1/2"	36"	49 1/2"		
Mobile home	32"	45 1/4"	34"	48 1/2"	36"	47 1/2"		

CORNER HEARTH		ALDERI	EA T4			ALDERL	EA T5		ALDERLEA T6				
(Extended to wall)	Α	С	D	E	Α	С	D	E	Α	С	D	Е	
* Minimum	32"	53 1/4"	50 3/8"	25"	34"	49 7/8"	47 3/8"	23 1/4"	36"	53 1/4"	50 3/8"	25"	
Residential, single wall, vert/horz connector	32"	58 7/8"	53"	30 3/8"	34"	65 7/8"	58 3/8"	34 1/4"	36"	59"	54 3/8"	29"	
Residential, double wall, vert/horz connector	32"	49"	46"	23 3/8"	34"	55 5/8"	51 3/8"	27 1/4"	36"	59"	54 3/8"	29"	
Mobile home	32"	56 1/8"	51"	28 3/8"	34"	61 1/4"	55 3/8"	31 1/4"	36"	60 3/8"	55 3/8"	30"	

MINIMUM CLEARANCES TO COMBUSTIBLES







RESIDENTIAL

SINGLE WALL CONNECTOR*

* Pipe shield may be required - consult local codes

		S	traight l i Vertical (Straight Installation Horizontal Connector				ner llation	Alcove Installation			
MODEL	From top of stove to ceiling	Α	A B C D				В	С	D	E	F	G	Н	1	J
T4	58"	15"	14"	20 3/4"	26"	13"	14"	18 3/4"	26"	10"	22 5/8"	N/A	N/A	N/A	N/A
T5	56"	12"	18"	22"	30"	8"	14"	18"	26"	11"	25"	N/A	N/A	N/A	N/A
T6	54"	9"	12"	17 1/2"	24 3/4"	10"	12"	18 1/2"	24 3/4"	4"	18 3/4"	N/A	N/A	N/A	N/A

RESIDENTIAL

DOUBLE WALL CONNECTOR

			•	nstallatio Connecto			Straight Installation Horizontal Connector				er tion	Alcove Installation **			
MODEL	From top of stove to ceiling	Α	A B C D				В	С	D	E	F	G	Н	I	J
T4	58"	7"	12"	12 3/4"	24"	7"	12"	12 3/4"	24"	3"	15 5/8"	11"	12"	16 3/4"	24"
T5	56"	5"	14"	15"	26"	5"	14"	15"	26"	4"	18"	10"	16"	20"	28"
T6	54"	6"	12"	14 1/2"	24 3/4"	10"	12"	18 1/2"	24 3/4"	4"	18 3/4"	9"	15"	17 1/2"	27 3/4"

^{**} Please refer to manuals for minimum height and maximum depth of alcove.

MOBILE HOME

DOUBLE WALL CONNECTOR

				nstallatio Connecto		Straight Installation Horizontal Connector				Corne Installa		Alcove Installation			
MODEL	From top of stove to ceiling	Α	A B C D				В	С	D	E	F	G	Н	1	J
T4	58"	12"	12"	17 3/4"	24"	N/A	N/A	N/A	N/A	8"	20 5/8"	N/A	N/A	N/A	N/A
T5	56"	8"	16"	18"	28"	N/A	N/A	N/A	N/A	8"	22"	N/A	N/A	N/A	N/A
T6	54"	7"	14"	15 1/2"	26 3/4"	N/A	N/A	N/A	N/A	5"	19 3/4"	N/A	N/A	N/A	N/A



... where tradition, craftsmanship and performance meet.



For your assurance of warmth and peace of mind, we further our commitment to quality and innovation with Pacific Energy's Limited Lifetime Warranty – we know of no better cast iron woodstove guarantee.







PACIFIC ENERGY FIREPLACE PRODUCTS LTD.

www.pacificenergy.net